Ideal portable emergency power for outdoor camping and home use



EP02 Series Portable Power Station Ideal portable emergency power for outdoor camping and home use

CAPP Date: Para MacRook Lights Date: TV Galan Konte Pad Plant



This product is suitable for outdoor rescue, outdoor camping, outdoor photography, outdoor emergency. It can satisfy the power supply of mortgage electrical equipment such as mobile phone, computer, network router, etc., as well as all kinds of high-power electrical equipment or lighting fixtures

Technical parameter

Model No	EP01-600	EP01-1000	EP01-1500
Battery type	LiFePO ₄		
Rated capacity (Wh)	595	992	1448
AC Output rated power (W)	600	1200	1800
AC Output peak power (W)	1000	3600	4000
AC Output rated voltage (V)	100~120/220~240		
AC Output frequency (Hz)	50/60		
DC 12V & Car lighter output rated power (A)	10		
Wireless charging output power(W)	no such function		
USB-A Output	5V/3A; 9V2A; 12V3A; 15V3A(18W Max)		
USB-C Output	5V/3A;9V3A;12V3A;15V3A;20V/3A(60W Max)		
Input Voltage (V)	12~30		
Input Power (W)	100	200	2*200
Time of charging (H)	6		
Working temperature(°C)	-0~+40		
Service life of battery (times)	2000		
LED light power (W)	7 5		
Dimensions (mm)	267*197*247	330*220*289	385*243*340
Net weight (kg)	6.8	11	15

Image: Context Participation <th



This product is widely used in mobile office, outdoor recreation, self-driving travel, medical rescue, fire emergency rescue, power equipment repair, environmental protection, emergency communication support, and power storage and backup places.

Technical parameter

Model No	EP02-500	EP02-1200	
Battery type	LiFePO ₄		
Rated capacity (Wh)	518 1210		
AC Output rated power (W)	500	1500	
AC Output peak power (W)	1000	3000	
AC Output rated voltage (V)	100~120/220~240		
AC Output frequency (Hz)	50/60		
DC 12V & Car lighter output rated power (A)	10		
Wireless charging output power(W)	10*2	no such function	
USB-A Output	5V/3A		
USB-C Output	5~20V/45W		
Input Voltage (V)	12~28		
Input Power (W)	120		
Time of charging (H)	6		
Working temperature(°C)	-20~+55		
Service life of battery (times)	≥2000		
LED light power (W)	5W		
Dimensions (mm)	288*160*230 400*210*29		
Net weight (kg)	6.7	16	

Туре	monocrystalline silicon	
Output power	100W	
Conversion efficiency	20%	
Solar battery chip	18V	
Short-circuit current	5.28A	
DC output	18V/100W	
Dimensions (mm)	415*370*35mm Fold 1670*415*5mm Unfold	
Net weight (kg)	3.6	



Dimensions (mm)	390*440*65mm	
Net weight (kg)	1	
Apply to	EP01-600 / EP01-1000	

Ideal portable emergency power for outdoor camping and home use

TORMIN Zhejiang TORMIN Electrical Co., Ltd EP02 Series Portable Power Station Ideal portable emergency power for outdoor camping and home use

Image: Control in the state Image: Control in the state





This product is suitable for outdoor construction, camping electricity, AC/DC/ car charge /USB (PD) power supply mode, no matter computer mobile phone and other outdoor office equipment, uav, camera, head, live lighting and other outdoor shooting equipment, power tools, ventilators and other outdoor medical equipment can be easily done. It is the power supply companion of rv, fishing, etc. More application scenarios for you to discover.

Technical parameter

EP03-500

Model No	EP03-500	EP03-1000	
Battery type	LiFePO4		
Rated capacity (Wh)	460.8 1075		
AC Output rated power (W)	600	2000	
AC Output peak power (W)	800	2500	
AC Output rated voltage (V)	90-240		
AC Output frequency (Hz)	50/60		
DC 12V & Car lighter output rated power (A)	10		
Wireless charging output power(W)	10		
USB-A Output	5V3A;9V2.4A		
USB-C Output	5V3A ; 9V2.4A ; 12V3A ; 15V3A ; 20V1.25A		
Input Voltage (V)	12~36		
Input Power (W)	200		
Time of charging (H)	6		
Working temperature(°C)	-10~+70		
Service life of battery (times)	2000		
LED light power (W)	12		
Dimensions (mm)	336*194*240 450*240*320		
Net weight (kg)	7.5	16.5	

Image: Image:



This product is suitable for camping equipment, AGV car, logistics truck, medical equipment, mechanical equipment, power tools, electric vehicles, electronic products and other applications.

Technical parameter

Model No	EP04-300	EP04-500	EP01-1000
Battery type	18650Ternary lithium		
Rated capacity (Wh)	288.6	519	999
AC Output rated power (W)	330	500	1000
AC Output peak power (W)	360	590	1180
AC Output rated voltage (V)	110-240		
AC Output frequency (Hz)	50/60		
DC 12V & Car lighter output rated power (A)	10		
Wireless charging output power(W)	5 10		
USB-A Output	12V1.5A; 9V2A; 5V2.5A		
USB-C Output	12V1.5A; 9V2A; 5V2.5A		
Input Voltage (V)	12~24		
Input Power (W)	45 100		
Time of charging (H)	6		
Working temperature(°C)	-0~+40		
Service life of battery (times)	2000		
LED light power (W)	3 5		
Dimensions (mm)	205*155*165	290*194*200	290*202*202
Net weight (kg)	3.3	6.8	8.5